

0349228

Amara 7W Dimmable LED Downlight - Tri-CCT - IP54

Features

- Perfect for almost any room
- Dimmable with trailing-edge dimmers
- Suitable for installation with insulated ceiling - IC-4 Rating
- 70mm cut-out
- Tri-CCT selectable



ORDERING INFORMATION

Order code	17933
Description	Lumio Amara 7W Downlight IP54 TRI-CCT - White
Item Code	0349228

MECHANICAL

Adjustability	Fixed
Fitting Colour	White
IC Rating	IC-4
IC-4 rating has been conducted at the products maximum working Temperature Range (C) in line with Australian standards. This provides the required safety when covered with insulation and used in Australian Environments.	
Installation Type	Recessed
IP Rating	IP54 Front Face Only

ELECTRICAL

Electrical Rating	Class II
Input Current	0.04 A
Input Frequency	50 Hz
Input voltage	220-240V~
Maximum Wattage	7 W
Power Factor	0.9
System Max Wattage	7 W
Working Temp Range	0 to 45 °C

LAMP

Beam Angle	90 °
CCT Configuration	TRI-CCT
CRI	>80
Lamp/LED Current	195 mA
Lamp/LED voltage	32 V
System Efficiency	80 lm/W

LED LIFETIME

LED Lifetime Rating	35000
---------------------	-------

COLOUR TEMPERATURE

6 Watts	
Warm White (3000 K)	500 lm
Cool White (4000 K)	550 lm
DayLight (5700 K)	520 lm

DRIVER

Dimmable	Yes
Driver Included	Yes
Integrated Driver	No
Driver Mode	Constant Current
Flex & Plug or Lead Length	0.9 mm



COMPLIANCE

Standards	AS/NZS 60598.1 AS/NZS 60598.2.2 AS/NZS 61347.1 AS/NZS 61347.2.13 AS CISPR 15
-----------	------------------------------------------------------------------------------------------

DIMENSIONS

Cutout	70-75 mm
Product Diameter	85 mm
Product Height	40 mm

LINE DRAWINGS

AMARA